

## Wavelength Dependence of Cirrus Optical Depth

10 December 2001

Prepared by

D. K. LYNCH and S. M. MAZUK  
Space Science Applications Laboratory  
Laboratory Operations

Prepared for

SPACE AND MISSILE SYSTEMS CENTER  
AIR FORCE SPACE COMMAND  
2430 E. El Segundo Boulevard  
Los Angeles Air Force Base, CA 90245


Engineering and Technology Group

APPROVED FOR PUBLIC RELEASE;  
DISTRIBUTION UNLIMITED

This report was submitted by The Aerospace Corporation, El Segundo, CA 90245-4691, under Contract No. F04701-00-C-0009 with the Space and Missile Systems Center, 2430 E. El Segundo Blvd., Los Angeles Air Force Base, CA 90245. It was reviewed and approved for The Aerospace Corporation by J. A. Hackwell, Principal Director, Space Science Applications Laboratory. Michael Zambrana was the project officer for the Mission-Oriented Investigation and Experimentation (MOIE) program.

This report has been reviewed by the Public Affairs Office (PAS) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nationals.

This technical report has been reviewed and is approved for publication. Publication of this report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.

  
\_\_\_\_\_  
Michael Zambrana  
SMC/AXE

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</small>					
1. REPORT DATE (DD-MM-YYYY) 10-12-2001		2. REPORT TYPE		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE  Wavelength Dependence of Cirrus Optical Depth				5a. CONTRACT NUMBER F04701-00-C-0009	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)  D. K. Lynch and S. M. Mazuk				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  The Aerospace Corporation Laboratory Operations El Segundo, CA 90245-4691				8. PERFORMING ORGANIZATION REPORT NUMBER  TR-2002(8570)-1	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Space and Missile Systems Center Air Force Space Command 2430 E. El Segundo Blvd. Los Angeles Air Force Base, CA 90245				10. SPONSOR/MONITOR'S ACRONYM(S) SMC	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) SMC-TR-02-10	
12. DISTRIBUTION/AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT  The normalized wavelength-dependent optical depth of the two cirrus cloud models resident in MODTRAN 4 ("standard" and "subvisual") is computed along with the scattering and absorption components. The wavelength-dependent asymmetry parameter is also calculated. We find that the optical depths as a function of wavelength are significantly different for the two models, most of which is attributable to particle size effects.					
15. SUBJECT TERMS  Cirrus, Optical depth, Scattering, Absorption, Extinction, Spectra, Clouds					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES  11	19a. NAME OF RESPONSIBLE PERSON David Lynch
a. REPORT UNCLASSIFIED	b. ABSTRACT UNCLASSIFIED	c. THIS PAGE UNCLASSIFIED			19b. TELEPHONE NUMBER (include area code) (310)336-6686

## **Acknowledgment**

This work was supported by the United States Air Force Space and Missile Systems Center through the Mission-Oriented Investigation and Experimentation program, under contract F4701-00-C-0009.

## Contents

1. Introduction .....	1
2. Calculations .....	3
3. Summary and Conclusions.....	9
References.....	11

## Figures

1. The particle size distribution for the subvisual model contains more particles $\text{cm}^{-3}$ , and they are on average much smaller ( $a_{\text{mode}} = 4 \mu\text{m}$ ) than for the standard model ( $a_{\text{mode}} = 64 \mu\text{m}$ ). .....	4
2. The extinction coefficient, $K_E$ , for the subvisual model displays significantly more spectral structure than does the standard model.....	5
3. The components of extinction coefficient, $K_E$ , (absorption $K_A$ and scattering $K_S$ ) as a function of wavelength for the subvisual cirrus model in MODTRAN4. ....	6
4. The components of the extinction coefficient, $K_E$ , (absorption $K_A$ and scattering $K_S$ ) as a function of wavelength for the standard cirrus model in MODTRAN4. ....	6
5. The asymmetry parameter, $g$ , as a function of wavelength is between about 0.75 and 1.0 for both models.....	7

## Table

1. Scattering and Absorption Size Parameters for the Standard and Subvisual Cirrus Cloud Mode Particle Sizes in MODTRAN4.....	5
---	---

## 1. Introduction

Cirrus clouds<sup>1</sup> are frequently characterized by their optical depth at a specific wavelength, usually in the visible near  $0.55\ \mu\text{m}$  or at lidar wavelengths  $0.6328\ \mu\text{m}$ . For example, subvisual cirrus is defined as "... any high clouds composed primarily of ice ... and whose vertical visible optical depth is 0.03 or less."<sup>2</sup> It is frequently necessary to know the optical depth at a different wavelength. In this report, we compute the optical depth as a function of wavelength for the two cirrus cloud models resident in MODTRAN 4 ("standard" and "subvisual").

The Moderate Resolution Transmittance (MODTRAN) code, developed by the Air Force Research Lab (AFRL), calculates atmospheric transmittance and radiance for frequencies (in wavenumbers) from 0 to  $50,000\ \text{cm}^{-1}$  at moderate spectral resolution, primarily  $2\ \text{cm}^{-1}$  ( $20\ \text{cm}^{-1}$  in the UV).<sup>3</sup> The development of the MODTRAN model was motivated by the need for higher spectral resolution than was available in the Low-Resolution Transmittance (LOWTRAN7). MODTRAN's capabilities include spherical refractive geometry, solar and lunar source functions, scattering (Rayleigh, Mie, single and multiple), and default atmosphere profiles (gases, aerosols, clouds, fogs, and rain). MODTRAN version 4 release 1 is the most current release and was used for these calculations.

## 2. Calculations

The defining input parameters for both cirrus cloud models in MODTRAN4<sup>4</sup> are extinction coefficient  $K_E$  ( $\text{km}^{-1}$ ), cloud thickness  $L$  (derived from the specified cloud base height and cloud top height), cloud base height, and choice of cloud model, standard or subvisual. The optical depth,  $\tau$ , of the cloud is defined as

$$\tau = K_E L = (K_S + K_A) L, \quad (1)$$

where  $K_E$  is the extinction coefficient ( $\text{km}^{-1}$ ), and  $L$  is the cloud thickness.  $K_S$  and  $K_A$  are the scattering and absorption components of  $K_E$ , respectively.  $\tau$  is a unitless quantity.

The transmission,  $t$ , of the cloud is then given by

$$t = \exp(-K_E L) = \exp(-\tau). \quad (2)$$

The threshold optical depth for subvisual cirrus is 0.03, which corresponds to a transmission of 0.97. Note that when the optical depth is small, i.e.,  $\tau \ll 1$ , then the series expansion reveals

$$t = 1 - \tau + \tau^2/2! - \tau^3/3! \approx 1 - \tau, \quad (3)$$

which handily reproduces  $t \approx 0.97$  when  $\tau = 0.03$ .

Owing to particle size effects and variations of the index of refraction with wavelength,  $\lambda$ ,  $\tau$  also varies with wavelength. The wavelength dependence for  $K_E$ ,  $K_A$ , and asymmetry are hard-coded into MODTRAN4 for both cirrus cloud models. These values were computed by Shettle et al.<sup>5</sup> based on Warren's optical constants<sup>6</sup> and Shettle et al.'s assumed particle size distribution given by the log-normal distribution function:

$$dN/da = n(a) = a^\alpha \exp(-ba), \quad (4)$$

where  $a$  is the particle radius, and  $a$ ,  $\alpha$ , and  $b$  are constants. Figure 1 shows the particle size distributions used to compute  $K_E$ . The mean (mode) particle radius  $a$  for the standard and subvisual models is 64  $\mu\text{m}$  and 4  $\mu\text{m}$ , respectively, and the calculations were performed under the assumption that all the particles are spherical.




Figure 1. The particle size distribution for the subvisual model contains more particles  $\text{cm}^{-3}$ , and they are on average much smaller ( $a_{\text{mode}} = 4 \mu\text{m}$ ) than for the standard model ( $a_{\text{mode}} = 64 \mu\text{m}$ ).

Figure 2 shows the optical depth of both cloud models, normalized to unity at  $0.55 \mu\text{m}$ , extracted from MODTRAN4. Since  $\tau$  is proportional to  $K_E$ , this is essentially  $K_E$  normalized to unity at  $0.55 \mu\text{m}$ . It is obvious that the standard model's optical depth varies very little with wavelength, but the subvisual model's optical depth varies considerably. The reason for this is relatively simple, and relates to the particles' optical depth.

Small particles tend to be optically thin, and the large particles tend to be optically thick. This is best expressed in terms of the scattering size parameter  $X (= 2\pi a/\lambda)^{7,8}$  and the absorption size parameter  $\Omega (= 4\pi k a/\lambda)^9$ . These values are shown in Table 1, which is calculated for the mode particle sizes 4 and  $64 \mu\text{m}$ , using the optical constants of Warren.<sup>6</sup> Thus, the small particles' behavior is dominated by absorption, while the large particles' behavior is dominated by scattering. The composition of a large particle ( $X$  or  $\Omega \gg 1$ ) is less important than its size because its extinction properties will be dominated by scattering. Extinction by small (optically thin,  $X$  or  $\Omega \ll 1$ ) particles, on the other hand, is more sensitive to composition (optical constants) because the actual absorptions play a relatively larger role.






Figure 2. The extinction coefficient,  $K_E$ , for the subvisual model displays significantly more spectral structure than does the standard model. The values for  $K_E$  are normalized to unity at  $0.55 \mu\text{m}$ .

Table 1. Scattering and Absorption Size Parameters for the Standard and Subvisual Cirrus Cloud Mode Particle Sizes in MODTRAN4

$\lambda(\mu\text{m})$	$a = 4 \mu\text{m}$		$a = 64 \mu\text{m}$	
	subvisual ( $\Omega \ll 1$ )		standard ( $X \gg 1$ )	
	$X$	$\Omega$	$X$	$\Omega$
2	13	0.01	201	0.19
4	6.3	0.02	100	0.3
6	4.2	0.27	67	4.3
8	3.4	0.07	50	1.2
10	2.5	0.08	40	1.4
12	2.1	0.32	33	5.2

The wavelength dependence of  $K_S$  and  $K_A$  for the subvisual cirrus model is shown in Figure 3, and that of the Standard cirrus model in Figure 4.




Figure 3. The components of extinction coefficient,  $K_E$ , (absorption  $K_A$  and scattering  $K_S$ ) as a function of wavelength for the subvisual cirrus model in MODTRAN4.




Figure 4. The components of the extinction coefficient,  $K_E$ , (absorption  $K_A$  and scattering  $K_S$ ) as a function of wavelength for the standard cirrus model in MODTRAN4.

The asymmetry parameter,  $g$ , characterizes the scattering of light for the particle as a whole. For pure forward scattering,  $g$  would be  $+1.0$ , and for pure backscattering,  $g$  would be  $-1.0$ . For a symmetric scatterer (like a Rayleigh scatterer),  $g$  would be zero. Figure 5 shows the asymmetry parameter,  $g$ , for both the standard and subvisual cirrus models as a function of wavelength. In both cases,  $g$  is between about 0.75 and 1.00, though the standard model is generally much closer to unity at all wavelengths. This is because the standard model has larger particles, and these are more efficient forward scatterers than the smaller particles that comprise the subvisual cirrus model.




Figure 5. The asymmetry parameter,  $g$ , as a function of wavelength is between about 0.75 and 1.0 for both models. The values for both models are greater than 1, indicating that the particles are primarily forward scatterers.

### **3. Summary and Conclusions**

The normalized wavelength-dependent optical depth of the two cirrus cloud models resident in MODTRAN 4 ("standard" and "subvisual") has been presented and decomposed into its scattering and absorption components. We find that the optical depth as a function of wavelength is significantly different for the two models, most of which is attributable to particle size effects. The wavelength-dependent asymmetry parameter is also presented, and shows similar particle size effects.

## References

1. Lynch, D. K., K. Sassen, D. Starr, and G. Stephens (editors), *CIRRUS*, Oxford University Press, Oxford (2001).
2. Lynch, D. K. and K. Sassen, "Subvisual Cirrus," *CIRRUS*, D. K. Lynch, K. Sassen, D. Starr, and G. Stephens, eds, Oxford University Press 2001.
3. Berk, L. S. Bernstein, and D. C. Robertson, "MODTRAN: A Moderate Resolution Model for LOWTRAN 7 (1989)," Air Force Geophysics Laboratory Technical Report GL-TR-89-0122, Hanscom AFB, MA.
4. Kneizys, F. X., Shettle, E. P., Abreu, L. W., Chetwynd, J. H., Anderson, G. P., Gallery, W. O., Selby, J. E. A., and Clough, S. A., "Users Guide to LOWTRAN 7," Tech. rep., Air Force Geophysics Laboratory AFGL 1986.
5. Shettle, E. P., Kneizys, F. X., Clough, S. A., Anderson, G. P., Abreu, L. W. and Chetwynd, J. H., 1986, "Cloud Models in LOWTRAN and FASCODE," Proc. CIDOS-1988 Workshop, D. Grantham and J. W. Snow (Eds.), 199-206.
6. Warren, S. G., "Optical constants of ice from the ultraviolet to the microwave," *Appl. Opt.* **23**, 1026-1225, (1984).
7. van de Hulst, H. C., *Light Scattering by Small Particles*, Wiley, NY, 1957; Dover, NY, 1981).
8. Bohren, C. F. and D. R. Huffman, *Absorption and scattering of light by small particles*, 1983, xiv + 530, Wiley, New York.
9. Lynch, David K. and Stephan Mazuk, "On the Size Parameter for Thermally Emitting Particles," *Applied Optics*, Lasers and Photonics Division, 38, 08/20, 5229-5231 (1999). Erratum: *Appl. Opt.* Vol. 38, p. 7467 (1999).

## LABORATORY OPERATIONS

The Aerospace Corporation functions as an "architect-engineer" for national security programs, specializing in advanced military space systems. The Corporation's Laboratory Operations supports the effective and timely development and operation of national security systems through scientific research and the application of advanced technology. Vital to the success of the Corporation is the technical staff's wide-ranging expertise and its ability to stay abreast of new technological developments and program support issues associated with rapidly evolving space systems. Contributing capabilities are provided by these individual organizations:

**Electronics and Photonics Laboratory:** Microelectronics, VLSI reliability, failure analysis, solid-state device physics, compound semiconductors, radiation effects, infrared and CCD detector devices, data storage and display technologies; lasers and electro-optics, solid state laser design, micro-optics, optical communications, and fiber optic sensors; atomic frequency standards, applied laser spectroscopy, laser chemistry, atmospheric propagation and beam control, LIDAR/LADAR remote sensing; solar cell and array testing and evaluation, battery electrochemistry, battery testing and evaluation.

**Space Materials Laboratory:** Evaluation and characterizations of new materials and processing techniques: metals, alloys, ceramics, polymers, thin films, and composites; development of advanced deposition processes; nondestructive evaluation, component failure analysis and reliability; structural mechanics, fracture mechanics, and stress corrosion; analysis and evaluation of materials at cryogenic and elevated temperatures; launch vehicle fluid mechanics, heat transfer and flight dynamics; aerothermodynamics; chemical and electric propulsion; environmental chemistry; combustion processes; space environment effects on materials, hardening and vulnerability assessment; contamination, thermal and structural control; lubrication and surface phenomena.

**Space Science Applications Laboratory:** Magnetospheric, auroral and cosmic ray physics, wave-particle interactions, magnetospheric plasma waves; atmospheric and ionospheric physics, density and composition of the upper atmosphere, remote sensing using atmospheric radiation; solar physics, infrared astronomy, infrared signature analysis; infrared surveillance, imaging, remote sensing, and hyperspectral imaging; effects of solar activity, magnetic storms and nuclear explosions on the Earth's atmosphere, ionosphere and magnetosphere; effects of electromagnetic and particulate radiations on space systems; space instrumentation, design fabrication and test; environmental chemistry, trace detection; atmospheric chemical reactions, atmospheric optics, light scattering, state-specific chemical reactions and radiative signatures of missile plumes.

**Center for Microtechnology:** Microelectromechanical systems (MEMS) for space applications; assessment of microtechnology space applications; laser micromachining; laser-surface physical and chemical interactions; micropropulsion; micro- and nanosatellite mission analysis; intelligent microinstruments for monitoring space and launch system environments.

**Office of Spectral Applications:** Multispectral and hyperspectral sensor development; data analysis and algorithm development; applications of multispectral and hyperspectral imagery to defense, civil space, commercial, and environmental missions.